


NOZZLE SCHEDULE					
MARK	SIZE	WALL THK.	NOZ. TYPE	RTG-PSI	FUNCTION
A	3"	.216"	RF-SO	150	INLET
B	3"	.216"	RF-SO	150	OUTLET
C	1 1/2"	--	FULL CPLG	3000	DRAIN
D	1/2"	--	HALF CPLG	6000	VENT

- NOTES:
1. FLANGE BOLT HOLES TO STRADDLE VESSEL Q'S.
 2. APPROX. WEIGHT:
 - a. DRY-74 lbs.
 - b. FLOODED(WATER)-99 lbs.
 3. UNIT IS PAINTED WITH A HIGH HEAT RESISTANT PAINT, SAFETY BLUE.

CONSTRUCTION	
A.S.M.E. SECTION VIII DIVISION I A.S.M.E. U-1 STAMP REQUIRED	
DESIGN SPECIFICATIONS	
DES. PRESS.	150 PSIG
DES. TEMP.	500° F.
CORR. ALL.	1/16"
FULL VACUUM	YES
HYDRO. TEST	195 PSIG
STRESS REL.	NONE REQ'D
RADIOGRAPH	NONE REQ'D
M.D.M.T	-20° F. @ 150 PSIG

REVISION: 0					
NO.	DESCRIPTION	BY DATE	NO.	DESCRIPTION	BY DATE
DIDION SEPARATOR COMPANY					
A DIVISION OF					
					
DIDION'S MECHANICAL					
<i>NOT BIGGEST....BEST!</i>					
PH: (419) 483-2226		WEB: didionseparator.com			
FX: (419) 483-4382		e-mail: dmech@didionsmech.com			
DESCRIPTION: HORIZONTAL/DOWN FLOW SEPARATOR					
MODEL#: DSL-3-150					
DRWN. JLD	DATE: 03/18/10	APPR.	DATE:		
CHK.	DATE:	APPR.	DATE:		
SCALE:	DRAWING NUMBER			REV.	SHEET
D.M. NO.	DSL-3-150-SALES			0	NO. 1 OF 1
P.O. NO.					