


TOP ORIENTATION VIEW



DIMENSIONAL VIEW

NOZZLE SCHEDULE				
MARK	SIZE	SPEC	NOZ. TYPE	FUNCTION
A	1/4"	6000#	CPLG	VENT
B	1/2"	6000#	CPLG	INLET
C	1/2"	6000#	CPLG	OUTLET
D	3/4"	6000#	CPLG	DRAIN

- NOTE: 1. DESIGNED, FABRICATED AND STAMPED IN ACCORDANCE WITH ASME CODE SECTION VII, DIV. 1.
2. SEPARATORS AVAILABLE IN CARBON STEEL, 304 & 316 STAINLESS STEEL, OR OPTIONAL ALLOYS UPON REQUEST.
3. ALL DIMENSIONS ARE IN INCHES
4. WEIGHT (DRY) = 32 LBS.

**CONSTRUCTION**  
A.S.M.E. SECTION VIII DIVISION I  
A.S.M.E. Ⓢ-U1 STAMP REQUIRED

DESIGN SPECIFICATIONS	
DES. PRESS.	500 PSIG
DES. TEMP.	650° F.
FULL VACUUM	YES
CORR. ALL.	1/16"
HYDRO. TEST	650 PSIG
STRESS REL.	NONE REQ'D
RADIOGRAPH	NONE REQ'D
M.D.M.T	-20° F. @ 500 PSIG

REVISION: 0			
NO.	DESCRIPTION	BY DATE	NO.

**DIDION SEPARATOR COMPANY**

A DIVISION OF



**DIDION'S MECHANICAL**

WEB: didionseparator.com

PH: (419) 483-2226

FX: (419) 483-4382

**NOT BIGGEST...BEST!**

e-mail: dmech@didionsmech.com

DESCRIPTION: HORIZONTAL FLOW SEPARATOR

MODEL#: DST-.5-NPT

SALES DRAWING

DRWN. JLD	DATE: 12/28/17	APPR.	DATE:
CHK.	DATE:	APPR.	DATE:
SCALE:	DRAWING NUMBER		REV.
D.M. NO.	DST-.5-NPT-SALES		0
P.O. NO.			SHEET NO. 1 OF 1

THIS DRAWING AND ALL INFORMATION ON IT IS THE PROPERTY OF DIDION'S MECHANICAL. IT IS CONFIDENTIAL AND IS GIVEN TO YOU FOR A LIMITED PURPOSE AND MUST BE RETURNED ON REQUEST. NEITHER THIS DRAWING NOR ANY PART OF IT NOR ANY INFORMATION CONCERNING IT MAY BE COPIED, EXHIBITED OR FURNISHED TO OTHERS NOR MAY PHOTOGRAPHS BE TAKEN OF ANY ARTICLE FABRICATED OR ASSEMBLED FROM THIS DRAWING WITHOUT CONSENT OF DIDION'S MECHANICAL.